

MD900-V2.30.A Update Installation Instructions

Mayer-EMI https://mayer-emi.at Discord: https://discord.gg/MEGZ8a8JCP

Table of contents

2 Downloads43 Copy to MEMI USB Stick54 Insert USB Stick65 Start Update Package75.1 Update Package86 Installer screen96.1 Installation done10	1 Download MD900 V2.30.A	3
3 Copy to MEMI USB Stick54 Insert USB Stick65 Start Update Package75.1 Update Package86 Installer screen96.1 Installation done10	2 Downloads	4
4 Insert USB Stick65 Start Update Package75.1 Update Package86 Installer screen96.1 Installation done10	3 Copy to MEMI USB Stick	5
5 Start Update Package75.1 Update Package86 Installer screen96.1 Installation done10	4 Insert USB Stick	6
5.1 Update Package86 Installer screen96.1 Installation done10	5 Start Update Package	7
6 Installer screen96.1 Installation done10	5.1 Update Package	8
6.1 Installation done 10	6 Installer screen	9
	6.1 Installation done	10
7 Check version 11	7 Check version	11



1 Download MD900 V2.30.A

- · Navigate to https://my.mayer-emi.at
- Navigate to Downloads / Software
- Open "MD900 XVAOS V2.30 Rev: A"



2 Downloads

Check "Files"

Download "MD900-XVAOS-V2.30.A-Update.md900.pkg"



MAYER

3 Copy to MEMI USB Stick

· Copy the File "MD900-XVAOS-V2.30.A-Update.md900.pkg" into the root directory of the MEMI USB Stick

Make sure to use the USB Stick delivered with the MD900

- or -

Ensure the USB Stick has the name "MEMI"



MAYER

4 Insert USB Stick

1. Insert the USB Stick in one of the USB Host Ports on the back of the MD900



5 Start Update Package

Wait, until the question of found package(s) to process are shown:

- 1. Press first wheel knob to start installation
- 2. Press second wheel knob to skip

Doublecheck to ensure to process the wanted package.



MAYER

5.1 Update Package

Detail Message of Package-Name to start



6 Installer screen

Wait for the installer screen to show up. Doublecheck the version to install.

- 1. Press first wheel knob to start installation
- 2. Press fourth wheel knop to exit the installer without installation



6.1 Installation done

After installation has started, the installation steps are logged.

1. Press fourth wheel knob to exit installation program after installation

The synthesizer engine will start up.



7 Check version

- 1. Select the DIAG pane on the touch screen
- 2. Check for Version "2.30 Rev:A"

ARRANGER MASTER SYNTI	H A VOICE A FX A ARP A DRUM CLIP MIDI DIA	SEQ/APR CLIPs
MIDI Input:	Event Filter:	FX MATRIX
	MIDI CLOCK	ARK. DRUM
	MIDI CC Used: 759472 kb	MASTER VOICE
	Notint assess the	
listen	MIDI NOTE	
22 22 6	46.1 C MD988 X-VA Sunthesizer OS Ver: 2.38 Rev:A	
S1 S2 EV	Care	
	\frown	
		ESC ENTER